

With a variety of lifting capacities and stroke lengths available, EQ Systems can provide a lifting or leveling system that fits your needs and specifications. These rugged, American made jacks can be purchased as part of a lifting/leveling system or individually to be added to your existing hydraulic system.

AM SERIES



AM shown with stand off bracket

SM SERIES



SM shown with stand off bracket



SM shown with double PO check valve and leg lock bars

HM SERIES



HM shown with double PO check valve and custom foot pad

	TUBE IN TUBE											
	AJ	AM				CT	SM				HM	OM
Capacity (each jack)	8k lbs	12k lbs				17k lbs	25k lbs				35k lbs	40k lbs
Dimension	3.5" x 3.5"	4" x 4"				4.5" x 4.5"	5" x 5"				5.5" x 5.5"	6.625" x 6.625"
Cylinder Bore	2"	2.5"				3"	3.5"				4"	4.5"
Stroke Length	24"	16"	20"	24"	30"	20"	16"	20"	24"	30"	20"	16"
Retracted Length	35.375"	27.25"	31.25"	35.25"	41.25"	33.125"	27.375"	31.375"	35.375"	41.375"	32.5"	32.75"
Extended Length	59.375"	42.3125"	50.3125"	58.3125"	70.3125"	53.125"	42.75"	50.75"	58.75"	70.75"	52.5"	48.75"
Weight*	75 lbs	67 lbs	76 lbs	85 lbs	98 lbs	108 lbs	116 lbs	103 lbs	130 lbs	135 lbs	167 lbs	170 lbs

* Weight of jacks are approximate due to custom brackets and foot pads that are available





FEATURES & OPTIONS

HYDRAULIC PUMPS

- One pump assembly operates all jack legs
- Variety of manual override options are available
- Heavy duty 12 or 24 volt
- Can be mounted in powder coated steel box or tray



SWITCHGEAR

- Switchgear made in-house
- Performance Verification Tested
- Braided nylon exterior for durability and protection
- Single, dual or quad switchgear available
- Custom lengths available




OPEN SPOOL MANIFOLD

- Dual or quad options
- Lift-truck style levers
- Reliable operation

OPTIONAL SAFETY FEATURES

- Pilot operated check—hydraulically locks leg in place
- Mechanical lock out bars—physically locks leg in extended position
- Keyed switchgear—prevents unauthorized use of the system



800-846-9659
www.eqsystems.us

EQS1004R2